



Jaroslav Sedláček **Floor-Fitting**
Plovoucí podlahy, Koberce, Pvc
Prodej-Pokládka
 mobil- 775 106 107
www.floor-fitting.cz

SPECIFICATION

Quality		: MAINSTONE
Product definition		: tufted loop pile
Gauge		: 1/10"
No. of tufts	ISO 1763	: ± 154000/m ² (± 128750 /yd ²)
Pile fibre		: 100% polyamide solution dyed
Pile weight		: 550 gr/m ² ± 5% (± 16 oz/yd ²)
Pile height	ISO 1766	: 3 mm ± 5%
Primary backing		: PA/PES non-woven - Colback
Tile backing		: Polyflex with glass fibre scrim and a non-woven fabric
Total thickness	ISO 1765	: 7 mm ± 5%
Total weight		: 4280 gr/m ² ± 7,5% (± 126 oz/yd ²)
Tile size		: 50 x 50 cm (± 19.7" x 19.7")
Tiles per box		: 20

PERFORMANCE

Use classification		: heavy contract Class 2
Castor chair test	EN 985	: A, continuous use
Abrasion	EN 1963	: pass
Vettermann test	ISO TR 10361/EN 1471	: pass
Thermal isolation	ISO 8302	: 0.10 m ² K/W
Dimensional stability	ISO 2551	: pass

ELECTROSTATIC PROPERTIES

Walk on test	EN 1815	: -0,2 kV
Horizontal electrical resistance	ISO CD 10965	: 8x10 ¹⁰ Ω
Vertical electrical resistance	ISO CD 10965	: 3x10 ¹⁰ Ω
Static loading		: anti-static

FLAME PROPERTIES

Reaction to fire	EN ISO 11925-2	
	EN ISO 9239-1	: C _n -s1
Hot metal nut test	BS 4790	: Low Radius

COLOUR FASTNESS PROPERTIES

Light	ISO 105 B02	: > 5.0
Rubbing, dry	ISO 105 X12	: 4.0
Rubbing, wet	ISO 105 X12	: 4.0
Shampoo	BS 1006	: 5.0
Water	ISO 105 E01	: 5.0
Water stains	TNO W 6024	: 4.5



GENERAL

Recommended maintenance:
 Pile direction:

Best results are obtained when cleaned with a dry shampoo method.
 Directional arrows are printed on the back of each tile.
 Best results are obtained when laid checkerboard