



PeVanHa b.v.  
TEGELTAPLIT  
CARPETTILES  
FLIESENTEPPICH

Jaroslav Sedláček **Floor-Fitting**  
Plovoucí podlahy, Koberce, Pvc  
Prodej-Pokládka  
mobil- 775 106 107  
[www.floor-fitting.cz](http://www.floor-fitting.cz)

## SPECIFICATION

Quality		: <b>OFFLINE</b>
Product definition		: tufted loop pile
Gauge		: 1/10"
No. of tufts	ISO 1763	: $\pm 217000/\text{m}^2$ ( $\pm 181440 /\text{yd}^2$ )
Pile fibre		: 100% polyamide – Antron Excel
Pile weight		: $650 \text{ gr}/\text{m}^2 \pm 5\%$ ( $\pm 19 \text{ oz}/\text{yd}^2$ )
Pile height	ISO 1766	: $3.2 \text{ mm} \pm 5\%$
Primary backing		: PA/PES non-woven - Colback
Tile backing		: Polyflex with glass fibre scrim and a non-woven fabric
Total thickness	ISO 1765	: $6.7 \text{ mm} \pm 5\%$
Total weight		: $4520 \text{ gr}/\text{m}^2 \pm 7,5\%$ ( $\pm 133 \text{ oz}/\text{yd}^2$ )
Tile size		: $50 \times 50 \text{ cm}$ ( $\pm 19.7'' \times 19.7''$ )
Tiles per box		: 20

## PERFORMANCE

Use classification		: heavy contract Class 33
Castor chair test	EN 985	: A, continuous use
Abrasion	EN 1963	: pass
Vettermann test	ISO TR 10361/EN 1471	: pass
Thermal isolation	ISO 8302	: $0.08 \text{ m}^2 \text{ K}/\text{W}$
Dimensional stability	ISO 2551	: pass

## ELECTROSTATIC PROPERTIES

Static electrical charging	EN 1815	: -0.2 kV
Stactic loading		: anti-static
Horizontal electrical resistance	ISO CD 10965	: $9 \times 10^7 \Omega$
Vertical electrical resistance	ISO CD 10965	: $4 \times 10^9 \Omega$
Electrical resistance	IBM/ICL	: pass

## FLAME PROPERTIES

Reaction to fire	EN ISO 11925-2 EN ISO 9239-1	: $C_{fl} - s1$
Hot metal nut test	BS 4790	: Low Radius

## COLOUR FASTNESS PROPERTIES

Light	ISO 105 B02	: 6-7
Rubbing, dry	ISO 105 X12	: 4.5
Rubbing, wet	ISO 105 X12	: 4.5
Water	ISO 105 E01	: 4.5
Shampoo	BS 1006	: 4.5
Water stains	EN 1307/F	: 5.0

## GENERAL

Recommended maintenance:  
Pile direction:

Best results are obtained when cleaned with a dry shampoo method.  
Directional arrows are printed on the back of each tile.  
Best results are obtained when laid checkerboard.

